

# 建表语句:查出别人如何建表的语句

疯狂代码 <http://www.CrazyCoder.cn/>     <http://www.CrazyCoder.cn/DataBase/Article17605.html>

```
conn system/manager
grant connect,resource to a identified by a;
grant connect,resource to b identified by b;
conn a/a
```

```
create table a(a number);
insert into a values(1);
insert into a values(2);
insert into a values(3);
```

```
create table b(a number,b varchar2(10));
insert into b values(1,'1111');
insert into b values(2,'2222');
insert into b values(3,'3333');
commit;
```

2、打开一个DOS窗口、先执行导出

```
E:\>exp a/a file=a.dmp log=loga.txt
```

```
Export: Release 8.1.6.0.0 - Production _disiblevent=logb.txt
```

```
Import: Release 8.1.6.0.0 - Production on 星期五 12月 1 22:29:49 2000
```

(c) Copyright 1999 Oracle Corporation. All rights reserved.

```
连接到: Oracle8i Enterprise Edition Release 8.1.6.0.0 - Production
With the Partitioning option
JServer Release 8.1.6.0.0 - Production
```

经由常规路径导出由EXPORT:V08.01.06创建的文件

已经完成ZHS16GBK字符集和ZHS16GBK NCHAR 字符集中的导入

. 正在将A的对象导入到 A

```
\\"CREATE TABLE \"A\" (\"A\" NUMBER) PCTFREE 10 PCTUSED 40 INITRANS 1 MAXTRANS 25\"  
\\5 LOGGING STORAGE(INITIAL 131072 NEXT 65536 MINEXTENTS 1 MAXEXTENTS 2147483\"  
\\645 PCTINCREASE 50 FREELISTS 1 FREELIST GROUPS 1 BUFFER_POOL DEFAULT) TABLE\"  
\\SPACE \\SYSTEM\\\"  
.. 正在跳过表 \"A\"
```

```
\\"CREATE TABLE \"B\" (\"A\" NUMBER, \"B\" VARCHAR2(10)) PCTFREE 10 PCTUSED 40 INIT\"  
\\RANS 1 MAXTRANS 255 LOGGING STORAGE(INITIAL 131072 NEXT 65536 MINEXTENTS 1 \"  
\\MAXEXTENTS 2147483645 PCTINCREASE 50 FREELISTS 1 FREELIST GROUPS 1 BUFFER_P\"  
\\OOL DEFAULT) TABLESPACE \\SYSTEM\\\"  
.. 正在跳过表 \"B\"
```

成功终止导入，但出现警告。

E:\\>

4、使用编辑器打开logb.txt，里面可以看到建表语句

2008-9-26 0:22:44

疯狂代码 <http://www.CrazyCoder.cn/>